


## DOUBLE BOLT CLAMPS



PLATED IRON PART #	HOSE OD SIZE RANGE		TORQUE IN FT. LBS.
	FROM	TO	
DBC-20A	1.750	2.047	27
DBC-20B	1.109	2.297	27
DBC-20C	2.313	2.625	40
DBC-20D	2.500	2.750	40
DBC-30A	2.750	3.068	60
DBC-30B	3.063	3.375	60
DBC-30C	3.250	3.500	60
DBC-30D	3.500	3.813	40
DBC-40A	3.781	4.063	40
DBC-40B	4.031	4.281	40
DBC-40C	4.250	4.938	60
DBC-50A	4.500	5.250	60
DBC-50B	5.125	5.688	60
DBC-50C	5.688	5.938	60
DBC-60A	5.938	6.500	60
DBC-60B	6.500	7.563	60
DBC-80A	7.688	8.188	125
DBC-80B	8.250	8.875	125
DBC-80C	8.938	9.875	125
DBC-10A	9.938	11.375	125
DBC-12A	11.188	13.000	125
DBC-12B	12.188	14.000	200
DBC-14A	13.188	15.000	200
DBC-16A	15.063	17.500	260

### \*FEATURES

- Inner surface has dual gripping ridges.
- Bolt lugs are reinforced to prevent bending out of alignment.
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance.
- Measure hose OD accurately before ordering clamps.